



Ref. Certif. No.

SE-113578

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Battery driven nutrunner

Name and address of the applicant

Ets Georges Renault
38 rue Bobby Sands, 44818 St Herblain
FRANCE

Name and address of the manufacturer

Same as applicant

Name and address of the factory

Atlas Copco Industrial Technique AB
Tierpsverken, Maskinvägen 4, 815 44 Tierp
SWEDEN

Note: When more than one factory, please report on page 2

☐ Additional Information on page 2

Ratings and principal characteristics

18VDC, 36VDC

Trademark / Brand (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

EL***-***-**-*

Additional information (if necessary may also be reported on page 2)

☒ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62841-1:2014
IEC 62841-2-2:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

2402266STO-001, 2402266STO-002

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Torshamnsgatan 43
Box 1103
SE-164 22 Kista, Sweden

Date: 15 March, 2024

intertek

Signature:

Anneli Averland Johansson

Additional information

The nutrunner can be powered by either a 18V or 36V battery.
The tool is compatible with the separately sold accessories:

Crowfoot – An extension to reach in inconvenient spaces

Speed setting unit – A module to manually adjust the rotational speed of the tool

The name and address of the manufacturer of the speed setting unit is as follows:

EOLANE Combrée
ZA de l'ombrée
Bd Jean Baptiste Colbert
49520 Combrée

Type designation key EL ***-*_*-*_*

First asterisk	Can be B, S or C. B = firmware with single Pset (PREMIUM). S = firmware with multiple Pset (PREMIUM) C = WiFi communicating tool (WIRELESS).
Second asterisk	Second asterisk: H or omitted, omitted = 90° angle gear box for angle tools H = 110° angle gear box
Third asterisk	Rated max. torque value in Nm. Value in following range: 2.5, 3, 6, 7, 8, 12, 15, 30, 45, 60.
Fourth asterisk	Rated max. speed in Rpm. Value in following range: 130, 140, 160, 180, 260, 300, 360, 400, 480, 600, 670, 800, 880, 900, 1000, 1250, 1550.
Fifth asterisk	Can be P or A: P = Pistol grip handle. A = Straight handle P for pistol tools with 1/4" hexagonal output.
Sixth asterisk	Output shaft type: Omitted = can be Square drive 1/4", 3/8" or 1/2", or Hexa female 1/4" 4S = Square drive 1/4" 10S = Square drive 3/8" 4Q = Hexa. Female 1/4" SQ1/2 = Square drive 1/2"
Seventh asterisk	Can be "Z", "W" or omitted: Z = Zigbee wireless communication module W = WiFi wireless communication module
Eighth asterisk	Default rotation: Omitted = clockwise, CCW = counterclockwise
Nineth asterisk	Specific attachment for GFA accessory: Omitted = no attachment DU = compatible with GFA type "closed crowfoot" DUO = compatible with GFA type "open crowfoot"

This product also complies with:
EN 62841-1:2015 + AC:2015 + A11:2022
EN 62841-2-2:2014 + AC:2015
BS EN 62841-1:2015+A11:2022
BS EN 62841-2-2:2014
CAN/CSA C22.2 No. 62841-1:15
CAN/CSA C22.2 No. 62841-2-2:16
UL 62841-1:2015
UL 62841-2-2:2016

Date: 15 March, 2024

Signature:

