



Ref. Certif. No.

**SE-113362**

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME**

**CB TEST CERTIFICATE**

Product

Battery driven nutrunner

Name and address of the applicant

Ets Georges Renault  
38 rue Bobby Sands, 44818 St Herblain  
FRANCE

Name and address of the manufacturer

Same as applicant

Name and address of the factory

Same as applicant

Note: When more than one factory, please report on page 2

Additional Information on page 2

Ratings and principal characteristics

18VDC, 36VDC

Trademark / Brand (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

EPB\*\*-\*\*-\*

Additional information (if necessary may also be reported on page 2)

Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62841-1:2014  
IEC 62841-2-2:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

2400506STO-001, 2400506STO-002

This CB Test Certificate is issued by the National Certification Body

**Intertek Semko AB**  
Torshamnsgatan 43  
Box 1103  
SE-164 22 Kista, Sweden

Date: 14 February, 2024

**intertek**

Signature:  Anneli Averland Johansson

**Additional information**

The nutrunner can be powered by either a 18V or 36V battery.  
The tool is compatible with the separately sold accessories:

The tool can be used with the following accessories:

- Tracker – accessory is designed to measure a distance between the tool and the tracking base system, using UltraWide Band (UWB) waves. Tracker has no impact on the safety aspects of the tool
- BCR – Bar Code Reader
- Crowfoot – An extension to reach in inconvenient spaces

Type key:

EPB\*\*-\*.~.\*

First asterisk	Can be A, C or omitted. Omitted and A refers to non-communicating tool. C refers to communicating tool with different level of software functionalities.
Second asterisk	The maximum torque of the tool in Nm.
Third asterisk	The no load speed of the tool in rpm.
Fourth asterisk	The type of output of the tool (Q4 for 1/4" hexagonal output or 10S for 3/8" square output).
Fifth asterisk	Fifth asterisk can be DU, M32 or omitted

DU for EPB with crowfoot facility - A version of threaded front housing and gear box allowing to attach a crowfoot accessory

M32 for EPB with torque multiplier facility - A version of threaded front housing allowing to attach a torque multiplier accessory

This product also complies with:

EN 62841-1:2015 + AC:2015 + A11:2022

EN 62841-2-2:2014 + AC:2015

BS EN 62841-1:2015 + AC:2015

BS EN 62841-2-2:2014 + AC:2015

CSA C22.2 No. 62841-1:15 (R2020)

CSA C22.2 No. 62841-2-2:16

UL 62841-1:2015

UL 62841-2-2:2016

Date: 14 February, 2024

Signature:

